

10/13/2008 2:28:16 PM

2010	0.36	0.51	0.37	0.00	0.00	0.03	0.03	0.00	0.03	0.03	59.52
Building 10/01/2009-06/01/2010	0.07	0.51	0.36	0.00	0.00	0.03	0.03	0.00	0.03	0.03	59.18
Building Off Road Diesel	0.07	0.49	0.26	0.00	0.00	0.03	0.03	0.00	0.03	0.03	48.24
Building Vendor Trips	0.00	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	2.20
Building Worker Trips	0.00	0.01	0.09	0.00	0.00	0.00	0.00	0.00	0.00	0.00	8.74
Coating 06/01/2010-06/30/2010	0.29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.34
Architectural Coating	0.29	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Coating Worker Trips	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.34

Phase Assumptions

Phase: Fine Grading 6/1/2009 - 9/1/2009 - Default Fine Site Grading Description

Total Acres Disturbed: 3.67

Maximum Daily Acreage Disturbed: 0.92

Fugitive Dust Level of Detail: Default

20 lbs per acre-day

On Road Truck Travel (VMT): 0

Off-Road Equipment:

1 Graders (174 hp) operating at a 0.61 load factor for 6 hours per day

1 Rubber Tired Dozers (357 hp) operating at a 0.59 load factor for 6 hours per day

1 Tractors/Loaders/Backhoes (108 hp) operating at a 0.55 load factor for 7 hours per day

1 Water Trucks (189 hp) operating at a 0.5 load factor for 8 hours per day

Phase: Paving 9/1/2009 - 10/1/2009 - Default Paving Description

Acres to be Paved: 0.92

Off-Road Equipment:

4 Cement and Mortar Mixers (10 hp) operating at a 0.56 load factor for 6 hours per day

1 Pavers (100 hp) operating at a 0.62 load factor for 7 hours per day

1 Rollers (95 hp) operating at a 0.56 load factor for 7 hours per day

1 Tractors/Loaders/Backhoes (108 hp) operating at a 0.55 load factor for 7 hours per day

Phase: Building Construction 10/1/2009 - 6/1/2010 - Default Building Construction Description

Off-Road Equipment:

10/13/2008 2:28:16 PM

1 Cranes (399 hp) operating at a 0.43 load factor for 4 hours per day

2 Forklifts (145 hp) operating at a 0.3 load factor for 6 hours per day

1 Tractors/Loaders/Backhoes (108 hp) operating at a 0.55 load factor for 8 hours per day

Phase: Architectural Coating 6/1/2010 - 6/30/2010 - Default Architectural Coating Description

Rule: Residential Interior Coatings begins 1/1/2005 ends 12/31/2040 specifies a VOC of 250

Rule: Residential Exterior Coatings begins 1/1/2005 ends 12/31/2040 specifies a VOC of 250

Rule: Nonresidential Interior Coatings begins 1/1/2005 ends 12/31/2040 specifies a VOC of 250

Rule: Nonresidential Exterior Coatings begins 1/1/2005 ends 12/31/2040 specifies a VOC of 250